



# S15

## Subwoofer

S15 subwoofer is equipped with one powerful specific 15 " Fitalpro neodymium driver with 4" voice coil powered by the last generation of Powersoft Class D amplifier with DSP on board.

AUDIOFOCUS T-ligned + reflex design subwoofer delivers exceptional sensitivity and reaches 135 dB max SPL.

Its very compact size makes it extremely well suited for discreet configurations.

Perfect companion for low reinforcement of VENU series.



<b>Type</b>	Vented T-ligned - Passive/Active
<b>Nominal Impedance</b>	Passive: 8Ω
<b>Power handling RMS / Peak</b>	Passive: 700W RMS / 1400W Peak Active: 1000W RMS / 2400W Peak
<b>Frequency range @-3dBspl</b>	Passive: 50 Hz - 1,0 kHz Active: 42 Hz - 100 Hz (extended preset)
<b>Sensitivity spl 2πsr</b>	101 dB
<b>SPL@ Peak power</b>	Passive: 132,5 dB Active: 135 dB
<b>Components</b>	15" LF Fitalpro Custom made, 4" Voice coil
<b>Line Connectors</b>	Active: Balanced 1 x IN, 1 x OUT Neutrik© XLR
<b>Front connection for Cardio</b>	NO
<b>HP Connectors</b>	Passive: 2x Neutrik© speakON linked
<b>Construction</b>	Birch marine Plywood 15 & 24 mm
<b>Finish</b>	High resistant Polyurea coating
<b>Dimensions (h x w x d)</b>	485 x 580 x 520 mm 19,09" x 22,83" x 20,47"
<b>Weight</b>	Passive: 34 kg / 75 lb Active: 35 kg / 77 lb
<b>Mounting accessories</b>	M20 screw & 35 mm compatible flange

// Preliminary data // Preliminary data // Preliminary data // Preliminary data // Preliminary data // Preliminary data // Preliminary data // Preliminary data // Preliminary data //